

# Melbourne Rotomould 3060 Litre

Front View



Rear View Close-Up



Rear View



## Features and Benefits

- Factory installed Davey Rainbank automatic mains switchover system
- Garden pump option available
- Tank only option increases capacity of existing 3060 system, or install own pump and fittings
- 10 year guarantee on tank only
- Designed and made in Australia
- Configuration suits most applications
- UV stabilised food grade polyethylene
- Large range of colours
- Mosquito proof inlet and overflow strainers
- ISO 9001 quality certified system
- AS/NZS 4766 certified tank



# 3060L

## Rough In Diagram

**Tank Site:** The tank site must be a suitably designed fully supporting base which is flat, level and smooth. No allowance for differential settlement has been made and we recommend that the tank be installed on a suitably designed reinforced concrete slab overlying stable foundation material to ensure the quality of the base is maintained for the life of the tank. If used, sand or other consolidated fill must be boxed to prevent washing away. The proposed tank site must be at least the same size as the footprint of tank. To allow for the expansion of tanks when full slimline tanks require 50mm clearance from a solid structure.

**Tank Inlet:** Inlet pipe diameter should not exceed the overflow pipe diameter to prevent water back flowing out of the strainer. Leave enough space from the end of the inlet pipe so that the inlet strainer may be periodically checked and removed for cleaning as required.

**Tank Overflow:** Pressure fit the overflow strainer to allow for cleaning and removal. Overflow must be directed clear of the tank base to prevent it washing away.

